



E2B-M12LN08-M1-B1

Proximity sensor, LITE, inductive, nickel-brass, long body, M12, unshielded, 8 mm, DC, 3-wire, PNP-NO, M12 plug-in

| | |
|---------------------------|----------------------|
| Size | M12 |
| Mounting type | Non-flush |
| Sensing distance | 8 mm |
| Output type | PNP |
| Operation mode | NO |
| Connection method | Connector M12 |
| Material housing | Brass, nickel plated |
| Cable specifications | - |
| Overall length of sensor | 74 mm |
| Thread length | 47 mm |
| Degree of protection (IP) | IP67 |

İlgili ürünler



M12 Konnektörler ve Kablo Setleri

Her uygulama için endüstriyel konnektörler ve kablo setleri

CAD Kütüphanesi



E2B Cylindrical Proximity Sensor Veri Sayfası

EN PDF 6,6 MB



E2B- Talimat Sayfası

EN PDF 1,02 MB



EAC Mark removal Üretimden Kaldırılma Bildirimi

EN PDF 221 KB



Proximity Sensors Broşür

TR PDF 2,91 MB

WEB SİTESİ KULLANIM KOŞULLARI

Bu PDF belgesi, 22 August, 2024 tarihinde OMRON Endüstriyel Otomasyon Avrupa web sitesinden oluşturulmuştur. [yasal duyurular](#) için buraya tıklayın.