



## E2B-M18LS08-WP-B1 2M

Proximity sensor, LITE, inductive, nickel-brass, long body, M18, shielded, 8 mm, DC, 3-wire, PNP-NO, 2 m cable

<b>Size</b>	M18
<b>Mounting type</b>	Quasi-flush
<b>Sensing distance</b>	8 mm
<b>Output type</b>	PNP
<b>Operation mode</b>	NO
<b>Connection method</b>	Cable
<b>Material housing</b>	Brass, nickel plated
<b>Cable specifications</b>	PVC
<b>Cable length</b>	2 m
<b>Overall length of sensor</b>	78 mm
<b>Thread length</b>	58 mm
<b>Degree of protection (IP)</b>	IP67

## CAD Kütüphanesi



### E2B Cylindrical Proximity Sensor Veri Sayfası

EN PDF 6,6 MB



### E2B- Talimat Sayfası

EN PDF 1,02 MB



### EAC Mark removal Üretimden Kaldırılma Bildirimi

EN PDF 221 KB



### Proximity Sensors Broşür

TR PDF 2,91 MB

#### WEB SİTESİ KULLANIM KOŞULLARI

Bu PDF belgesi, 26 August, 2024 tarihinde OMRON Endüstriyel Otomasyon Avrupa web sitesinden oluşturulmuştur. [yasal duyurular](#) için buraya tıklayın.